

SOPRA Primer D41

Solvent Based Bituminous Waterproofing Primer

Description

SOPRA Primer D41 is a low viscosity bituminous solution in a selected solvent acting as a primer for all types of waterproofing membranes.

Uses

- * Damp and waterproofing for porous surfaces.
- * Primer for all hot and cold applied waterproofing membrane.
- * Can be used for both vertical and horizontal surfaces.

Advantages

- * Single component.
- * Quick drying.
- * Good damproofing action.
- * Economical.
- * Easy application.

Standard Compliance

ASTM D 41

Packaging

20 litre pails or 200 litre drums.

Storage

12 months storage life when stored in original containers at between 5°C and 35°C.

Properties

Form	Liquid
Colour	Black
Viscosity @ 25, °C, cps	30-80
Penetration @ 25 °C	20-50

Application Instructions

Surface Preparation

All surfaces must be sound, clean and free from contamination such as oil and grease.

Application

SOPRA Primer D41 should be mixed well before application. It can be applied using a brush, roller or spray at a rate of 200-250.g/m².

Curing

SOPRA Primer D41 should be left to dry and cure naturally. Overcoating should be carried out within 24 hours of priming.

Precautions

Health and Safety

SOPRA Primer D41 is non - hazardous. It should not be swallowed or allowed to come into contact with skin or eyes. Suitable protective goggles and gloves should be worn. In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice. When contact with the skin is made, wash off immediately with soap and water. If swallowed, seek medical attention immediately, do not induce vomiting.