

SOPRA JOINT 500

BITUMEN MASTIC

DESCRIPTION

SOPRA JOINT 500 is a Black bituminouse paste suitable for application by trowel or spatule

APPLICATION

SOPRA JOINT 500 is particulary recomnded for sealing horizontal joints (expansion and construction joint) in public - works, engineering buildings, industries, motorawy joints, parking areas, industrial floors, warehouses, sewage tanks, terraced roof crack sealing, etc.

SITE INSTRUCTIONS

Joint preparation Ensure that the joint surfces are completely dry and clean. remove all drit, dust, grease and oil. **SOPRA** JOINT 500 must always be supported by a film backing ensure that any expansion filler is lightly packed in the joint and that no voids or gaps exist at base of sealing slot.

PRIMING

Primer is not necessary on dry concrete.

SAFE HANDING

flammable, store and use away from the sources of ignition. Keep packing tightly closed after use in an enclosed space ensure thorough ventilation to avoid accumulation of vapore. To clean tools and hands use kerosene or gas oil, then

clean hands soap and water. resistance to solvents.

Resists water, salt solution, and dilute alkaline and acid solutions. Dos not resist oils nor organice solvents.

RESISTANCE TO HEAT

The cured film dose not sag flow under normal service conditions

FLEXIBILITY

Provides a soft flexible coating.

PACKAGING

5 Gal./pail

1 Gal./can.