

# SOPRA WOOD BOND

## Adhesive and bonding agent for wood work

### DESCRIPTION

**SOPRA WOOD BOND** is an aqueous solution based on Vinyl Acetate Homopolymer, non toxic, used as supper bonding agent for wood and paper works.

After application of **SOPRA WOOD BOND** on clean and dry surface of wood, it need 6-10 minutes to dry under the normal temperature (drying period changes subject to the temperature and humidity level).

**SOPRA WOOD BOND** is a high quality product, contains no additives, solid content is about 45% active materials. It has a high potential of bonding and gives transparent, strong and elastic film.

### STANDARDS

Complies to ASTM D 3236

ASTM D 2345-68

### SPECIFICATIONS

Type of polymer	Homopolymers.
Solid contents	45+2
pH	4-5
Viscosity (Brookfield RTV)	400-500 Piose 6/10
Emulsifying system	An ionic
Plasticiser content	7%
Mechanical stability	Positive.

High temperature stability

(At 150oC after 2 hours)

Positive.

### PACKAGING

1 Litre/ Can.

1 US Gallon/ Can.

20 Litres/ Pail.

210 Litres/ Drum.

### WARRANTY

Information contained in this document is given to the best of our knowledge and based on extensive testing in no event can it be considered as a warranty involving our liability in case of misapplication. A trial before application will ensure that the product conforms to the required conditions for use our specialists will assist in solving any difficulties encountered by the user.