

SOPRA Tile WR

Water Resistant Ceramic Tile Adhesive

Description

SOPRA Tile WR is a white/grey cement based adhesive powder to which water is added before application. It is composed of selected binders, graded fillers and other additives.

Uses

SOPRA Tile WR is a high quality dry set adhesive for permanent fixing of ceramic floor and wall tiles. It is specially formulated for use in damp and submerged areas, such as swimming pool, foundations, bathrooms, etc.

Standard Compliance

BS 5980 Type 1, class A

Packaging

25 kg bags.

Storage

12 months storage life when stored in a cool and dry place.

Properties

Form

Colour

Coverage, kg/m²
@ 3mm thickness

Powder

White & Grey

5

Application Instructions

Surface Preparation

The backing surface must be sound, clean and free from any trace of oil or paint. The surface should be dampened a few hours before application of SOPRA Tile WR.

Mixing

Add 4-5 litres of clean water per 25 kg of SOPRA Tile WR powder and mix until a uniform, lump-free consistency is achieved. Leave the mix to stand for 10 minutes, then stir it before use.

Application

Spread mixed SOPRA Tile WR on to the surface to a uniform thickness of 3-4 mm. then comb horizontally. Place tiles firmly on to the adhesive bed ensuring good contact with a twisting motion. Apply mixed SOPRA Tile WR up to a working area of not more than one square meter at a time. Joint grouting with SOPRA Joint Grout should be carried out after 24 hours.

Precautions

Health and Safety

SOPRA Tile WR is non-hazardous. It should not be swallowed or allowed to come into contact with skin or eyes. Suitable protective goggles and gloves should be worn. In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice. When contact with the skin is made, wash off immediately with soap and water. If swallowed, seek medical attention immediately, do not induce vomiting.