

# SOPRA Joint Grout

## Cementitious Grout For Tile Joints

### Description

SOPRA Joint Grout is a cement based powder, blended with synthetic polymers and fillers to grout tile joints.

### Mixing

Mix the SOPRA Joint Grout with 5-6 litres water to obtain a smooth thick consistency. Leave to stand for about 10 minutes before using.

### Uses

SOPRA Joint Grout is used for filling tile joints in swimming pools, kitchen, bathroom, etc. It can also be used for exterior applications.

### Application

Apply the mixed grout to the tile joints with squeegee, brush or sponge, working it in thoroughly to ensure total compaction. Remove surplus grout with a damp sponge. Polish the tiles when the job is complete with a clean dry cloth.

### Standard Compliance

ASTM C 109  
ASTM C 230  
ASTM C 348

### Precautions

#### Health and Safety

SOPRA Joint Grout is non-hazardous. It should not be swallowed or allowed to come into contact with skin or eyes. Suitable protective goggles and gloves should be worn. In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice. When contact with the skin is made, wash off immediately with soap and water. If swallowed, seek medical attention immediately, do not induce vomiting.

### Packaging

15 kg bag  
5 Kg bag

### Storage

12 months storage life when stored in a cool and dry place.

### Technical Support

SOPRA provides on-site assistance and consulting services on projects when requested. Technical data sheets on other SOPRA products and guidance on their use are available on request.

### Properties

Form	Powder
Colour	yellow, dark green, dark blue, dark red, light brown, black, white and grey

### Application Instructions

#### Joint Preparation

Ensure that joints are clean and there is no excess mortar in them. Tile should not be grouted until at least 24 hours after fixing.