

Sopra Crack Filler

Extra Fine Finish Filler

Description

SopraCrack Filler is a dry cementitious powder for plaster. It contains blended cements, graded sand and additives to improve consistency and workability.

Uses

- * Filling of cracks and holes up to 4 mm wide in exterior and interior concrete, masonry or plaster-based substrates.
- * Residential and industrial structures.

Advantages

- * Easy to use, only requires the addition of clean cold water.
- * Durable finish.
- * Paintable once hardened.
- * Prevents ingress of water and aggressive chemical agents through cracks and holes.

Packaging

5 and 20 kg bag.

Storage

12 months storage life when stored in original unopened bags at between 2 and 35 °C in a dry and shaded place.

Application Instructions

Surface Preparation

The surface should be clean, free from standing water and all contaminants such as oil, grease, laitance, paint, or corrosion products. Any contamination should be removed by mechanical means to produce a sound substrate. The surface should be washed with clean water to remove all dust. It should be wetted prior to application of Sopra Crack Filler. It should not be applied to surfaces which are exposed to running water.

Mixing

Complete bags should be mixed using a mechanically powered grout mixer. Each 20 kg bag requires 6-8 litres of clean cold water. Ensure that the mixer is damp inside but free of standing water before commencing mixing, add the pre-measured quantity of clean cold water. Sopra Crack Filler should be slowly added to the mixer while stirring continuously for at least three minutes to achieve a uniform consistency.

Application

Apply the mixed Sopra Crack Filler firmly into the cracks or holes in the substrate using either a spatula or a putty knife.

Curing

Where Sopra Crack Filler is used for the smoothing of surfaces, especially outdoors, it should be well cured with water for 3-5 days.