

SOPRA TILE PASTE W.P.

Ready to use adhesive past - waterproof

DESCRIPTION

SOPRA TILE PASTE W.P. is a ready to use pre-mixed adhesive specially formulated for fixing tiles both in damp and totally submerged condition i.e. swimming pool, fountain, etc.

USES

To fix ceramic wall and floor tiles in bathrooms, kitchens, toilets, suitable backgrounds including brick, gypsum plaster, sand cement renders, gypsum board, glazed bricks etc.

STANDARDS

SOPRA TILE PASTE W.P. complies with
BS 5980 Type 2 Class B
BS 5385 Part 1
ANSI A 136-1 Organic adhesive.

COMPOSITION

SOPRA TILE PASTE W.P. is composed of specially selected filler, styrene acrylic bonding agent, additives and fungicides.

BACKING PREPARATION

The backing should be sound, clean, dustless and without any trace of oil or paint.

APPLICATION

Apply **SOPRA** TILE PASTE W.P. to the background to a depth of 3mm, working in a maximum area of one square metre at a time. Form horizontal ribs in the adhesive using a notched trowel. Begining at the top or bottom press the tile in twisting action and wipe off the surplus adhesive with a damp cloth. Complete each square metre, in the same way before proceeding to the next section. If the adhesive is spread over a large area, skinning might occur and cause ad-

hesive failure.

JOINT

Joint grouting with **SOPRA** Tile Grout after 24 hours.

PROPERTIES

Density	:	1.7 (+/-) 0.1
Pot Life	:	30 minutes.
Colour	:	White
Working Temp	:	50C - 45oC.
Workability Tme	:	20oC - 35 minutes. 30oC - 25 minutes.

COVERAGE

Approximately 2-3 kg of **SOPRA** TILE PAST W.P. will cover one square metre, when applied with 3mm thickness.

PACKAGING

SOPRA TILE PASTE W.P. is supplied in 25 kg/ pail

STORAGE

SOPRA TILE PASTE W.P. should be stored in cool dry place.

SHELF LIFE

The shelf life of this product is 12 months if, stored in cool dry place.

HEALTH AND SAFETY

As with all material of this type adequate ventilation should be ensured during work.

Take care to avoid contact with eyes.

TECHNICAL ASSISTANCE

SOPRA will provide technical advice on the selection ond application of its products and will also provide on-site demonsration to assist the user.